



Model _____	GX 11 - 15 S
Carrying Capacity _____	11,000kg
Cubic Capacity _____	15m ³
Maximum Trailer Speed _____	20mph
Body _____	Dimensions: 5140x2450x1290mm Hydraulically operated rear door Access ladder outside and inside body Rope hooks on every body panel
Floor Bearers _____	80x40 steel box section
Body Frame _____	80x80 steel box section
Top Rail _____	80x40 steel box section
Floor _____	5mm steel
Sides _____	3mm steel
Chassis _____	200x100 box section
Top Chassis _____	150x100 box section
Axles _____	90mm 8 stud, 300x135 brakes
Suspension _____	Sprung suspension
Drawbar _____	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy 40mm tow eye welded to rear chassis
Wheel Centres _____	8 stud, fully welded high speed rims
Tyres _____	Remould 385/65Rx22.5 Tyres Mud wings and spray suppression flaps
Braking _____	Hydraulic braking system Ratchet style parking brake
Lighting _____	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with light guards Front marker lights Side marker lights High level rear marker lights Amber warning light
Tipping Mechanism _____	Twin 3 stage 3 1/2" chrome plated tipping rams 25mm ram pins with grease points 60mm hinge bar with bushes and grease points
Paint _____	Finished with 120 microns of two pack acrylic high gloss paint
Optional Extras _____	Fast tow trailer with air braking, ABS & LSV, Silage Sides, Roll over cover, Grain hatch, Flotation tyres, Granning 125mm ø 10 stud axles, 420x180 brakes, High level road lights