



Model _____	GX 15 - FT
Length _____	26ft to 36ft
Carrying Capacity _____	15,000kg
Maximum Trailer Speed _____	20mph
Body _____	Standard width 2500mm (8'2")
Floor Bearers _____	100x50 channel
	Rope hook on every floor bearer
Floor _____	28mm Keruing or 4mm steel
Side Rave _____	125x75x8 steel angle
Chassis _____	250x150 box section
Axles _____	Granning 125mm ø 10 stud, 420x180 brakes
Suspension _____	Granning overslung 4 spring suspension
Drawbar _____	Heavy duty 40mm hitch eye
Wheel Centres _____	10 stud, fully welded high speed rims
Tyres _____	Remould 385/65Rx22.5
	Spray suppression flaps
Braking _____	Hydraulic braking system
	Ratchet style parking brake
Lighting _____	LED commercial road lighting system
	Connection to tractor: Removable electric coil
	Rear stop/tail/indicator lights
	Front marker lights
	Side marker lights
	Amber warning light
Paint _____	Finished with 120 microns of two pack acrylic high gloss paint
Optional Extras _____	600mm (2ft) rear harvest ladder
	1800mm (6ft) front and rear harvest ladders
	Fast tow trailer fitted with air braking, ABS & LSV
	Hydraulically operated catwalk
	Hydraulically operated box pusher
	Lockable plastic or stainless steel toolbox
Axle Option _____	Granning 125mm ø axles, 310x190 brakes with 435/55Rx19.5 tyres