



Model _____	GX 16 - 21 S
Carrying Capacity _____	16,000kg
Cubic Capacity _____	21m ³
Maximum Trailer Speed _____	20mph
Body _____	Dimensions: 6100x2450x1500mm Hydraulically operated rear door Access ladder outside and inside body Rope hooks on every body panel
Floor Bearers _____	80x40 steel box section
Body Frame _____	80x80 steel box section
Top Rail _____	80x40 steel box section
Floor _____	5mm steel
Sides _____	3mm steel
Chassis _____	250x150 box section
Top Chassis _____	150x100 box section
Axles _____	Granning 125mm ø 10 stud, 420x180 brakes
Suspension _____	Granning overslung 4 spring suspension 4 leaf springs
Drawbar _____	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy duty hitch eye welded to rear chassis
Wheel Centres _____	10 stud, fully welded high speed rims
Tyres _____	Remould 385/65Rx22.5 Tyres Mud wings and spray suppression flaps
Braking _____	Hydraulic braking system Ratchet style parking brake
Lighting _____	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with light guards Front marker lights Side marker lights High level rear marker lights Amber warning light
Tipping Mechanism _____	Twin 3 stage 4.25" chrome plated tipping rams 35mm ram pins with grease points 60mm hinge bar with bushes and grease points
Paint _____	Finished with 120 microns of two pack acrylic high gloss paint
Optional Extras _____	Fast tow trailer with air braking, ABS & LSV, Silage Sides, Roll over cover, Grain hatch, Front window/view grille, High level road lights, Flotation tyres