



<b>Model</b> _____	GX 18 - 23 S
<b>Carrying Capacity</b> _____	18,000kg
<b>Cubic Capacity</b> _____	23m <sup>3</sup>
<b>Maximum Trailer Speed</b> _____	20mph
<b>Body</b> _____	6700x2450x1500mm Hydraulically operated rear door Access ladder outside and inside body Rope hooks on every body panel
<b>Floor Bearers</b> _____	80x40 steel box section
<b>Body Frame</b> _____	80x80 steel box section
<b>Top Rail</b> _____	80x40 steel box section
<b>Floor</b> _____	5mm steel
<b>Sides</b> _____	3mm steel
<b>Chassis</b> _____	250x150 reinforced box section
<b>Top Chassis</b> _____	150x100 box section
<b>Axles</b> _____	Granning 125mm ø 10 stud, 420x180 brakes
<b>Suspension</b> _____	Granning overslung 4 spring suspension 4 leaf springs
<b>Drawbar</b> _____	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy duty hitch eye welded to rear chassis
<b>Wheel Centres</b> _____	10 stud, fully welded high speed rims
<b>Tyres</b> _____	Remould 385/65Rx22.5 Tyres Mud wings and spray suppression flaps
<b>Braking</b> _____	Hydraulic braking system Ratchet style parking brake
<b>Lighting</b> _____	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with light guards Front marker lights Side marker lights High level rear marker lights Amber warning light
<b>Tipping Mechanism</b> _____	Twin 3 stage 4.25" chrome plated tipping rams 35mm ram pins with grease points 60mm hinge bar with bushes and grease points
<b>Paint</b> _____	Finished with 120 microns of two pack acrylic high gloss paint
<b>Optional Extras</b> _____	Fast tow trailer with air braking, ABS & LSV, Silage Sides, Roll over cover, Grain hatch, Front window/grille, High level road lights, Flotation tyres