



Model _____	GX 20 - 24 S
Carrying Capacity _____	20,000kg
Cubic Capacity _____	24m ³
Maximum Trailer Speed _____	Fast-tow trailer 80kph
Body _____	Dimensions: 7600x2500x1370mm Hydraulically operated rear door Full width front view grille with perspex cover Access ladder outside and inside body Rope hooks on every body panel Grain hatch
Floor Bearers _____	80x40 steel box section
Body Frame _____	80x80 steel box section
Top Rail _____	80x80 steel box section
Floor _____	5mm steel
Sides _____	3mm steel
Chassis _____	300x200 box section
Top Chassis _____	200x100 box section
Axles _____	Granning 125mm ø 10 stud, 420x180 brakes
Suspension _____	Granning overslung 4 spring suspension 4 leaf springs
Drawbar _____	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy duty 40mm tow eyes welded to rear chassis
Wheel Centres _____	10 stud, fully welded high speed rims
Tyres _____	560/60Rx22.5 Tyres Mud wings and spray suppression flaps
Braking _____	Hydraulic. Air braking with ABS and LSV Connection to tractor: Dedicated ABS suzie Ratchet style parking brake
Lighting _____	Full LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with rear light guards Front marker lights Three side marker lights each side High level rear marker lights on door frame Amber warning light
Tipping Mechanism _____	Single 170mm 5 stage tipping ram 60mm hinge bar with bushes and grease points
Paint _____	Finished with 120 microns of two pack acrylic high gloss paint
Optional Extras _____	Roll over cover Silage Sides High level road lights