



<b>Model</b> _____	GX 8 - FT
<b>Length</b> _____	20ft to 22ft
<b>Carrying Capacity</b> _____	8,000kg
<b>Maximum Trailer Speed</b> _____	20mph
<b>Body</b> _____	Standard width 2500mm (8'2")
<b>Floor Bearers</b> _____	60x40 box section Rope hook on every floor bearer
<b>Floor</b> _____	28mm Keruing or 4mm steel
<b>Side Rave</b> _____	100x65x8 steel angle
<b>Chassis</b> _____	200x75 channel
<b>Axles</b> _____	70mm 6 stud, 300x60 brakes
<b>Suspension</b> _____	Sprung suspension
<b>Drawbar</b> _____	Heavy duty 40mm hitch eye
<b>Wheel Centres</b> _____	6 stud
<b>Tyres</b> _____	12.5/80x15.3 Spray suppression flaps
<b>Braking</b> _____	Hydraulic braking system Ratchet style parking brake
<b>Lighting</b> _____	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights Front marker lights Side marker lights Amber warning light
<b>Paint</b> _____	Finished with 120 microns of two pack acrylic high gloss paint
<b>Optional Extras</b> _____	600mm (2ft) rear harvest ladder 1800mm (6ft) front and rear harvest ladders