

GX 10 LL



SPECIFICATION

Model	GX 10 LL
Carrying Capacity	10,000kg
Length	6100mm
Floor Height	1040mm
Chassis	254x102 H beam
Floor Bearers	80x40 box section
Axles	90mm 8 stud axles, 300x135 brakes
Suspension	Mechanical underslung suspension
Tyres	435/50Rx19.5

STANDARD FEATURES

Headboard, ratchet style park brake, 8mm side rave with keyhole chain securing points, chain securing rings in the floor, rope hooks, LED commercial road lighting system, hydraulic braking system, sprung suspension, colour coded hydraulic nose grips and spray suppression flaps. Trailers are shotblasted then finished with two pack polyurethane Flexi Paint. Standard width is 2500mm.

OPTIONAL EXTRA ITEMS

- Fast tow trailer fitted with air braking, ABS and load sensing valve
- Hydraulic load sensing valve
- Bolt on spoon hitch
- Spray flaps front of wheels
- Spray flaps front of trailer
- Galvanised steel toolbox with lockable Stainless Steel lid
- Lockable plastic toolbox
- Steel chain storage box in floor
- Hydraulically operated beaver tail
- Hydraulically operated floor plate in beaver tail
- Removeable rear wedge
- Galvanised outriggers
- Illuminated extending marker boards (for outriggers)
- Rubber buffer on headboard
- Clip on aluminium ramps or hydraulic ramps
- Digger knuckle floor plate

NEED TO KNOW MORE?

Call **01467 681418**

Email sales@stewart-trailers.co.uk

