

GX 15 FT



SPECIFICATION

Model	GX 15 FT
Carrying Capacity	15,000kg
Length	7900mm to 9700mm (26ft to 32ft)
Floor height	1165mm on 385/65Rx22.5 1050mm on 435/50Rx19.5
Chassis	250x150 box section
Floor Bearers	100x50 steel channel
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 4 leaf springs
Tyres	Remould 385/65Rx22.5

STANDARD FEATURES

600mm headboard, ratchet style park brake, rope hooks on every floor bearer, LED commercial road lighting system, rear light guards, hydraulic braking system, sprung suspension, colour coded hydraulic nose grips, spray suppression flaps. Trailers are shotblasted then finished with two pack polyurethane Flexi Paint. Standard width is 2500mm.

OPTIONAL EXTRA ITEMS

Fast tow trailer fitted with air braking, ABS and load sensing valve

Hydraulic load sensing valve

Flotation tyres

Spray flaps front of wheels

Spray flaps front of trailer

Swivel hitch eye

Bolt on spoon hitch

Hydraulically operated catwalk with handrail

Hydraulically operated box pusher

Rear push bar

Galvanised steel toolbox with lockable
Stainless Steel lid

Lockable plastic toolbox

Work lights – rear facing

Air suspension

125mm ø 10 stud axles 310x190 brakes

NEED TO KNOW MORE?

Call **01467 681418**

Email sales@stewart-trailers.co.uk

