

GX 20 CM



SPECIFICATION

Model	GX 20 CM
Carrying Capacity	20,000kg
Cubic Capacity	14.1m ³
Height to top rail	2600mm
Tipped Height	6300mm
Body	5140 x 2500 x 1220mm
Chassis	300x150 box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 100mm wide 3 leaf springs
Tyres	Customer choice – recommend 560/60Rx22.5
Tipping Mechanism	Twin 3 stage 4.5" Ø chrome plated tipping rams

STANDARD FEATURES

Rear camera, audible door alarm, rear spray flaps, spray flaps front of trailer, LED work lights, wheel nut indicators, hydraulic rear door, Granning 125mm diameter 10 stud axles, fully welded high speed wheel rims, Granning mechanical suspension, hydraulic braking system, sprung drawbar, heavy duty 40mm tow eye, a tow eye welded to the rear of chassis, mud wings, LED commercial road lighting system, LED flashing warning light, rear light guards, ratchet style park brake, box section top chassis, chrome plated tipping rams, conspicuity tape around body, colour coded hydraulic hose grips. Trailers are shotblasted then finished with two pack polyurethane Flexi Paint.

OPTIONAL EXTRA ITEMS

Fast tow trailer fitted with air braking, ABS and load sensing valve

Rear drawbar with electric & hydraulic connections

On Board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon/hitch eye

Automatic Lubrication system

Stainless Steel light bar on back door

Hydraulic Flip Cover system

NEED TO KNOW MORE?

Call **01467 681418**

Email sales@stewart-trailers.co.uk

