

GX 22 LL



SPECIFICATION

Model	GX 22 LL
Carrying Capacity	22,000kg
Length	7.9m - 10m
Floor Height	1010mm
Chassis	250x150 box section
Floor Bearers	100x50 steel channel
Axles	Three 125mm Ø 10 stud, 310x190 brakes
Suspension	Mechanical underslung suspension
Tyres	435/50Rx19.5
Ramps	Hydraulically operated ramps

STANDARD FEATURES

Headboard, ratchet style park brake, 8mm side rave with keyhole chain securing points, chain securing rings in the floor, rope hooks, LED commercial road lighting system, hydraulic braking system, sprung suspension, colour coded hydraulic nose grips and spray suppression flaps. Trailers are shotblasted then finished with two pack polyurethane Flexi Paint. Standard width is 2500mm.

OPTIONAL EXTRA ITEMS

- Fast tow trailer fitted with air braking, ABS and load sensing valve
- Hydraulic load sensing valve
- Bolt on spoon hitch
- Spray flaps front of wheels
- Spray flaps front of trailer
- Galvanised steel toolbox with lockable Stainless Steel lid
- Lockable plastic toolbox
- Steel chain storage box in floor
- Air suspension
- Hydraulically operated beaver tail
- Hydraulically operated floor plate in beaver tail
- Removeable rear wedge
- Galvanised outriggers
- Illuminated extending marker boards (for outriggers)
- Rubber buffer on headboard
- Clip on aluminium ramps in place of hydraulic ramps
- Digger knuckle floor plate

NEED TO KNOW MORE?

Call **01467 681418**

Email sales@stewart-trailers.co.uk

