

PRO Series

PS 22 29 H



SPECIFICATION

Model	PS 22 29 H
Carrying Capacity	22,000kg
Cubic Capacity	29m ³ Silage 49m ³
Height to Top Rail	2950mm
Tipped Height	8950mm
Body	Hardox® 8400 x 2500 x 1500mm
Chassis	300x150 reinforced box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Air suspension
Tyres	560/60Rx22.5
Tipping Mechanism	Twin 4 stage 4.5" Ø chrome plated tipping rams

STANDARD FEATURES

Trailers shotblasted & finished in with two pack polyurethane Flexi Paint, Hardox® Body, Hydraulic rear door with door closing audible alarm, Front grille lined with Perspex, Fast tow trailer fitted with air braking, ABS and load sensing valve, Manual Roll Cover, Mud flaps front of trailer, front of wings and rear of trailer, Galvanised inspection ladder, Internal access steps, Sprung drawbar, Heavy duty 40mm hitch eye, LED commercial road lighting system, Side marker lights function as indicators, Rear light guards, LED flashing warning light with on/off switch, Rear view camera with wireless connection to tractor cab, Wheel nut indicators, Conspicuity tape around body, Colour coded hydraulic hose grips.

OPTIONAL EXTRA ITEMS

- Rear drawbar with electric & hydraulic connections
- On Board weigh cell system
- Valve to prevent door opening unless trailer tipped
- Swivel hitch eye
- Bolt on spoon hitch
- Automatic Lubrication system
- Grain hatch
- Grain sock
- Stainless Steel light bar on back door
- Silage Sides
- Hydraulic Flip Cover system
- Hydraulic side to side cover
- Steering axle
- Hydraulic fold down side panel
- Central Tyre Inflation System

NEED TO KNOW MORE?

Call **01467 681418**

Email sales@stewart-trailers.co.uk

