

LEGEND

SL 14 19 S



SPECIFICATION

Model	SL 14 19 S	SL 14 19 SS
Carrying Capacity	14,000kg	
Cubic Capacity	Grain 19m ³	
Height to top rail	2790mm	2840mm
Tipped Height	6300mm	
Body	6100 x 2500 x 1370mm 5000x2500x1500mm	
Chassis	250x150 box section	
Axles	125mm Ø 10 stud, 420x180 brakes	
Suspension	Mechanical suspension with 3 leaf springs	
Tyres	Customer choice – recommend 560/60R22.5	
Tipping Mechanism	Twin 3 stage 3.75"Ø chrome plated tipping rams	

STANDARD FEATURES

Rear camera, audible door alarm, rear spray flaps, spray flaps front of trailer, LED work lights, wheel nut indicators, hydraulic rear door, a galvanised inspection ladder, internal access steps, 5mm steel floor, 3mm steel sides, Granning 125mm diameter 10 stud axles, 8 or 10 stud fully welded high speed wheel rims, Granning mechanical suspension, hydraulic braking system, sprung drawbar, heavy duty 40mm tow eye, a tow eye welded to the rear of chassis, mud wings, LED commercial road lighting system, LED flashing warning light, rear light guards, ratchet style park brake, box section top chassis, chrome plated tipping rams, conspicuity tape around body, colour coded hydraulic hose grips. Trailers are shotblasted then finished with two pack polyurethane Flexi Paint.

OPTIONAL EXTRA ITEMS

- Fast tow trailer fitted with air braking, ABS and load sensing valve
- Hydraulic load sensing valve
- Front grille/window
- Rear drawbar with electric & hydraulic connections
- On Board weigh cell system
- Valve to prevent door opening unless trailer tipped
- Swivel hitch eye
- Bolt on spoon/hitch eye
- Automatic Lubrication system
- Grain hatch
- Grain sock
- Stainless Steel light bar on back door
- Silage Sides
- Manual Roll Cover
- Hydraulic Flip Cover system
- Hydraulic side to side cover
- Steering axle

NEED TO KNOW MORE?

Call **01467 681418**

Email sales@stewart-trailers.co.uk

