

# LEGEND

## SL 18 23 S



### SPECIFICATION

Model	SL 18 23 S
Carrying Capacity	20,000kg
Cubic Capacity	Grain 23m <sup>3</sup> Silage 39m <sup>3</sup>
Height to top rail	2850mm
Tipped Height	7150mm
Body	6700 x 2500 x 1500mm
Chassis	250x150 reinforced box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 4 leaf springs
Tyres	Customer choice – recommend 560/60Rx22.5
Tipping Mechanism	Twin 3 stage 4.25" Ø chrome plated tipping rams

### STANDARD FEATURES

Rear camera, audible door alarm, rear spray flaps, spray flaps front of trailer, LED work lights, wheel nut indicators, hydraulic rear door, a galvanised inspection ladder, internal access steps, 5mm steel floor, 3mm steel sides, Granning 125mm diameter 10 stud axles, 8 or 10 stud fully welded high speed wheel rims, Granning mechanical suspension, hydraulic braking system, sprung drawbar, heavy duty 40mm tow eye, a tow eye welded to the rear of chassis, mud wings, LED commercial road lighting system, LED flashing warning light, rear light guards, ratchet style park brake, box section top chassis, chrome plated tipping rams, conspicuity tape around body, colour coded hydraulic hose grips. Trailers are shotblasted then finished with two pack polyurethane Flexi Paint.

### OPTIONAL EXTRA ITEMS

- Fast tow trailer fitted with air braking, ABS and load sensing valve
- Hydraulic load sensing valve
- Front grille/window
- Rear drawbar with electric & hydraulic connections
- On Board weigh cell system
- Valve to prevent door opening unless trailer tipped
- Swivel hitch eye
- Bolt on spoon/hitch eye
- Automatic Lubrication system
- Grain hatch
- Grain sock
- Stainless Steel light bar on back door
- Silage Sides
- Manual Roll Cover
- Hydraulic Flip Cover system
- Hydraulic side to side cover
- Steering axle

### NEED TO KNOW MORE?

Call **01467 681418**

Email [sales@stewart-trailers.co.uk](mailto:sales@stewart-trailers.co.uk)

