

# LEGEND

## SL 20 26 S



### SPECIFICATION

Model	SL 20 26 S
Carrying Capacity	20,000kg
Cubic Capacity	grain 26m <sup>3</sup> silage 44m <sup>3</sup>
Height to top rail	2870mm
Tipped Height	7950mm
Body	7600 x 2500 x 1500mm
Chassis	300x200 box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 100mm wide 3 leaf springs
Tyres	Customer choice – recommend 560/60Rx22.5
Tipping Mechanism	Twin 3 stage 4.25" Ø chrome plated tipping rams

### STANDARD FEATURES

Trailers shotblasted & finished in with two pack polyurethane Flexi Paint, Box section body frame with 5mm steel floor and 3mm steel sides, Hydraulic rear door with door closing audible alarm, Hydraulic braking system, Air braking system with ABS and load sensing valve, Ratchet style park brake, Chrome plated tipping rams, Mud flaps front of trailer, front of wings and rear of trailer, Galvanised inspection ladder, Internal access steps, Front grille, Grain hatch, Sprung drawbar, Heavy duty 40mm hitch eye, LED commercial road lighting system, Side marker lights function as indicators, Rear light guards, LED flashing warning light with on/off switch, Rear view camera with wireless connection to tractor cab, Wheel nut indicators, Conspicuity tape around body, Colour coded hydraulic hose grips.

### OPTIONAL EXTRA ITEMS

Hydraulic load sensing valve
Rear drawbar with electric & hydraulic connections
On Board weigh cell system
Valve to prevent door opening unless trailer tipped
Swivel hitch eye
Bolt on spoon hitch
Automatic Lubrication system
Grain sock
Stainless Steel light bar on back door
Silage Sides
Manual Roll Cover
Hydraulic Flip Cover system
Hydraulic side to side cover
Steering axle

### NEED TO KNOW MORE?

Call **01467 681418**

Email [sales@stewart-trailers.co.uk](mailto:sales@stewart-trailers.co.uk)

