



CONSTRUCTION PRO CP15 H



ABS BRAKES

You do not need ABS on the tractor, the ABS system on the trailer takes its power from the brake light supply if there is no dedicated ABS supply.

SPECIFICATION

Model	Construction PRO CP15 H
Carrying Capacity	15,000kg
Unladen Weight	4,980kg
Cubic Capacity	11.4m ³
Height to top rail	2350mm
Tipped Height	6100mm
Body	5200 x 2450 x 1000mm Hardox Body
Chassis	250x150 box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 4 leaf springs
Tyres	Customer choice – recommend 560/60Rx22.5
Tipping Mechanism	Twin 3 stage 4.25" Ø chrome plated tipping ramps

OPTIONAL EXTRAS

Fast tow trailer fitted with air braking, ABS and load sensing valve

Hydraulic load sensing valve

Spray flaps front of mud wings

Spray flaps front of trailer

On board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon hitch

Autolube system

Stainless Steel light bar on back door

Work (reversing) lights at rear

Roll cover

Hydraulic Flip Cover system

Hydraulic side to side cover



+44 (0) 1467 681418



SALES@STEWART-TRAILERS.CO.UK