



## CONSTRUCTION PRO CP 20 H



### SPECIFICATION

<b>Model</b>	Construction PRO CP 20 H
<b>Carrying Capacity</b>	20,000kg
<b>Unladen Weight</b>	5,680kg
<b>Cubic Capacity</b>	13.7m <sup>3</sup>
<b>Height to top rail</b>	2400mm
<b>Tipped Height</b>	6850mm
<b>Body</b>	6050 x 2450 x 1000mm Hardox Body
<b>Chassis</b>	300x150 box section
<b>Axles</b>	125mm Ø 10 stud, 420x180 brakes
<b>Suspension</b>	Mechanical suspension with 100mm wide 3 leaf springs
<b>Tyres</b>	Customer choice – recommend 560/60Rx22.5
<b>Tipping Mechanism</b>	Twin 4 stage 4.5" Ø chrome plated tipping rams

### OPTIONAL EXTRAS

Fast tow trailer fitted with air braking, ABS and load sensing valve

Hydraulic load sensing valve

Spray flaps front of mud wings

Spray flaps front of trailer

On board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon hitch

Autolube system

Stainless Steel light bar on back door

Work (reversing) lights at rear

Roll cover

Hydraulic Flip Cover system

Hydraulic side to side cover