

## **TIPPING TRAILERS**

## GX 12 16 S



PROSeries PS 12 16 H



## **SPECIFICATION**

Model	GX 12 16 S PRO Series PS 12 16 H	
Carrying Capacity	12,000kg	
Unladen Weight	4,380kg	10
Cubic Capacity	grain 16m³	silage 28m³
Height to top rail	2600mm	3 N N
Tipped Height	5800mm	The State of the S
Body	5140 x 2450 x 1400mm	
Chassis	250x150 box section	
Axles	90mm 8 stud 300x135 brakes	
Suspension	Mechanical suspension	
Tyres	Customer choice – recommend 560/45Rx22.5	
Tipping Mechanism	Twin 3 stage 3.5"Ø chrome plated tipping rams	

## **OPTIONAL EXTRAS**

Fast tow trailer fitted with air braking, ABS and load sensing valve

Hydraulic load sensing valve

Front grille/window

Rear drawbar with electric & hydraulic connections

Spray flaps front of mud wings

Spray flaps front of trailer

On board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon hitch

Autolube system

Grain hatch

Grain sock

Stainless Steel light bar on back door

Work (reversing) lights at rear

Roll cover

Hydraulic Flip Cover system

Hydraulic side to side cover

