



TIPPING TRAILERS

GX 13 17 S



GX 13 17 SA

SPECIFICATION

Model	GX 13 17 S GX 13 17 SS	PRO Series PS 13 17 H PRO Series PS 13 17 HS
Carrying Capacity	13,000kg	
Unladen Weight	4860kg	
Cubic Capacity	grain 17m ³	silage 31 m ³
Height to top rail	2450mm	2610mm
Tipped Height	6200mm	6180mm
Body	GX 13 17 S GX 13 17 SS	6100 x 2450 x 1220mm 5500 x 2450 x 1370mm
Chassis	250x150 box section	
Axles	125mm Ø 10 stud, 420x180 brakes	
Suspension	Mechanical suspension with 3 leaf springs	
Tyres	Customer choice – recommend 560/45R22.5	
Tipping Mechanism	Twin 3 stage 3.75"Ø chrome plated tipping rams	

OPTIONAL EXTRAS

PRO Series PS 13 17 H with Hardox Body
Fast tow trailer fitted with air braking, ABS and load sensing valve
Hydraulic load sensing valve
Front grille/window
Rear drawbar with electric & hydraulic connections
Spray flaps front of mud wings
Spray flaps front of trailer
On board weigh cell system
Valve to prevent door opening unless trailer tipped
Swivel hitch eye
Bolt on spoon hitch
Autolube system
Grain hatch
Grain sock
Stainless Steel light bar on back door
Work (reversing) lights at rear
Roll cover
Hydraulic Flip Cover system
Hydraulic side to side cover