



TIPPING TRAILERS

GX 14 19 S



PRO Series PS 14 19 HS



PRO Series PS 14 19 HS

SPECIFICATION

Model	GX 14 19 S GX 14 19 SS	PRO Series PS 14 19 H PRO Series PS 14 19 HS
Carrying Capacity	14,000kg	
Unladen Weight	4950kg	
Cubic Capacity	grain 19m ³	silage 33 m ³
Height to top rail	GX 14 19 S GX 14 19 SS	2790mm 2840mm
Tipped Height	6300mm	6300mm
Body	GX 14 19 S GX 14 19 SS	6100 x 2450 x 1370mm 5000x2450x1500mm
Chassis	250x150 box section	
Axles	125mm Ø 10 stud, 420x180 brakes	
Suspension	Mechanical suspension with 3 leaf springs	
Tyres	Customer choice – recommend 560/60Rx22.5	
Tipping Mechanism	Twin 3 stage 3.75"Ø chrome plated tipping rams	

OPTIONAL EXTRAS

PRO Series PS 16 21 HS with Hardox Body

Fast tow trailer fitted with air braking, ABS and load sensing valve

Hydraulic load sensing valve

Front grille/window

Rear drawbar with electric & hydraulic connections

Spray flaps front of mud wings

Spray flaps front of trailer

On board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon hitch

Autolube system

Grain hatch

Grain sock

Stainless Steel light bar on back door

Work (reversing) lights at rear

Roll cover

Hydraulic Flip Cover system

Hydraulic side to side cover