



TIPPING TRAILERS

GX 18 23 S



PRO Series PS 18 23 H



SPECIFICATION

Model	GX 18 23 S	
Carrying Capacity	20,000kg	
Unladen Weight	5,900kg	
Cubic Capacity	grain 23m ³	silage 39m ³
Height to top rail	2850mm	
Tipped Height	7150mm	
Body	6700 x 2450 x 1500mm	
Chassis	250x150 reinforced box section	
Axles	125mm Ø 10 stud, 420x180 brakes	
Suspension	Mechanical suspension with 4 leaf springs	
Tyres	Customer choice – recommend 560/60Rx22.5	
Tipping Mechanism	Twin 3 stage 4.25" Ø chrome plated tipping rams	

OPTIONAL EXTRAS

PRO Series PS 18 23 H with Hardox Body

Fast tow trailer fitted with air braking, ABS and load sensing valve

Hydraulic load sensing valve

Front grille/window

Rear drawbar with electric & hydraulic connections

Spray flaps front of mud wings

Spray flaps front of trailer

On board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon hitch

Autolube system

Grain hatch

Grain sock

Stainless Steel light bar on back door

Work (reversing) lights at rear

Roll cover

Hydraulic Flip Cover system

Hydraulic side to side cover

