

SPECIFICATION

Model	GX 19 25 S PS 19 25 H
Carrying Capacity	19,000kg
Unladen Weight	6,250kg
Cubic Capacity	grain 25m ³ silage 42m ³
Height to top rail	2900mm
Tipped Height	7700mm
Body	7300 x 2450 x 1500mm
Chassis	300x150 reinforced box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 4 leaf springs
Tyres	Customer choice – recommend 560/60Rx22.5
Tipping Mechanism	Twin 3 stage 4.5" Ø chrome plated tipping rams

TIPPING TRAILERS

GX 19 25 S

OPTIONAL EXTRAS

- PRO Series PS 19 25 H with Hardox Body
- Fast tow trailer fitted with air braking, ABS and load sensing valve
- Hydraulic load sensing valve
- Front grille/window
- Rear drawbar with electric & hydraulic connections
- Spray flaps front of mud wings
- Spray flaps front of trailer
- On board weigh cell system
- Valve to prevent door opening unless trailer tipped
- Swivel hitch eye
- Bolt on spoon hitch
- Autolube system
- Grain hatch
- Grain sock
- Stainless Steel light bar on back door
- Work (reversing) lights at rear
- Roll cover
- Hydraulic Flip Cover system
- Hydraulic side to side cover



PRO Series PS 19 25 H

