



TIPPING TRAILERS

GX 20 26 S



SPECIFICATION

Model	GX 20 26 S PS 20 26 H	
Carrying Capacity	20,000kg	
Unladen Weight	6,700kg	
Cubic Capacity	grain 26m ³	silage 44m ³
Height to top rail	2870mm	
Tipped Height	7950mm	
Body	7600 x 2500 x 1500mm	
Chassis	300x200 box section	
Axles	125mm Ø 10 stud, 420x180 brakes	
Suspension	Mechanical suspension 100mm wide 3 leaf springs	
Tyres	BKT 560/60Rx22.5	
Tipping Mechanism	Twin 3 stage 4.5" Ø chrome plated tipping rams	
	Fast tow trailer fitted with air braking, ABS and load sensing valve	
	Front grille	
	Galvanised rack & pinion grain hatch	

OPTIONAL EXTRAS

PRO Series PS 20 26 H with Hardox Body

Hydraulic load sensing valve

Rear drawbar with electric & hydraulic connections

Spray flaps front of mud wings

Spray flaps front of trailer

On board weigh cell system

Valve to prevent door opening unless trailer tipped

Swivel hitch eye

Bolt on spoon hitch

Autolube system

Grain sock

Stainless Steel light bar on back door

Work (reversing) lights at rear

Roll cover

Hydraulic Flip Cover system

Hydraulic side to side cover