



TIPPING TRAILERS

PRO Series

PS 24 31 H



SPECIFICATION

| | | |
|--------------------|--|-------------------------|
| Model | PRO Series PS 24 31 H | |
| Carrying Capacity | 24,000kg | |
| Unladen Weight | 9,000kg | |
| Cubic Capacity | grain 31m ³ | silage 53m ³ |
| Height to top rail | 2880mm | |
| Tipped Height | 9100mm | |
| Body | Hardox 9000 x 2500 x 1500mm | |
| Chassis | 300x200 reinforced box section | |
| Axles | 125mm Ø 10 stud, 420x180 brakes | |
| Suspension | Mechanical suspension | |
| Tyres | BKT 560/60Rx22.5 | |
| Tipping Mechanism | Single 200mm Ø stage tipping ram with quick drop valve | |
| | Front grille | |
| | Air braking system with ABS & load sensing valve, spring parking brake | |
| | Bolt on hitch eye | |
| | Roll cover | |

OPTIONAL EXTRAS

| |
|---|
| Rear drawbar with electric & hydraulic connections |
| Spray flaps front of mud wings |
| Spray flaps front of trailer |
| On board weigh cell system |
| Valve to prevent door opening unless trailer tipped |
| Autolube system |
| Grain hatch |
| Grain sock |
| Stainless Steel light bar on back door |
| Work (reversing) lights |
| Hydraulic Flip Cover system |
| Hydraulic side to side cover |



UK REGULATIONS

The maximum weight allowed on the public highway is 31,000kg gross (tractor, trailer and load) with a further restriction on the combined weight of the trailer and load of 18,290kg



+44 (0) 1467 681418



SALES@STEWART-TRAILERS.CO.UK

