



TIPPING TRAILERS

RoadKing XV 20 26 S



PRO Series RoadKing XV 20 26 H

RoadKing

The Road King trailer is built on three axles with air suspension, with an optional rear steer axle for added manoeuvrability. Three axles on the trailer keep the maximum axle weight to 8 tonnes.

The Road King is fitted with an air braking system with load sensing and ABS and no hydraulic braking. The standard model also features a roll cover, front view grille and radial flotation tyres.

SPECIFICATION

Model	Road King XV 20 26 S PRO Series Road King XV 20 26 H	
Carrying Capacity	20,000kg	
Unladen Weight	7,500kg	
Cubic Capacity	grain 26m ³	silage 44m ³
Height to top rail	2950mm	
Tipped Height	7950mm	
Body	7600 x 2500 x 1500mm	
Chassis	300x150 reinforced box section	
Axles	125mm Ø 10 stud, 420x180 brakes	
Suspension	Air suspension	
Tyres	BKT 560/60Rx22.5	
Tipping Mechanism	Twin 3 stage 4.5" Ø chrome plated tipping rams	
	Air braking system with ABS and load sensing valve	
	Front grille	
	Spray flaps front of trailer	
	Roll cover	
	Grain Hatch	

OPTIONAL EXTRAS

PRO Series Road King XV 20 26 H with Hardox Body
Rear drawbar with electric & hydraulic connections
Spray flaps front of mud wings
On board weigh cell system
Valve to prevent door opening unless trailer tipped
Swivel hitch eye
Bolt on spoon hitch
Autolube system
Grain sock
Stainless Steel light bar on back door
Work (reversing) lights at rear
Hydraulic Flip Cover system
Hydraulic side to side cover